

## **EURO ROD FORMING ACCESSORIES**



#### **Combo Plate**

Size Washer Size Weight per pc Safe Working Load\* 120mm x 120mm 2.78 lbs 21,900 lbs



## **Round Wing Nut**

Size Washer Diameter Weight per pc 5/8" (15mm) 100mm 2.38 lbs Safe Working Load\* 21,900 lbs



### **Single Wing Nut**

Size Washer Size Weight per pc Safe Working Load\*
5/8" (15mm) 90mm x 60mm 0.75 lbs 21,900 lbs



## **Hex Couplings**

 Size
 Length
 Safe Working Load\*

 5/8" (15mm)
 50mm
 21,900 lbs

 5/8" (15mm)
 100mm
 21,900 lbs



## **Flange Nut**

SizeLengthSafe Working Load\*5/8" (15mm)35mm21,900 lbs



#### **Round Nut**

SizeLengthSafe Working Load\*5/8" (15mm)106mm21,900 lbs



#### **She Bolt Cones**

 Size
 Length
 Diameter

 5/8" (15mm)
 75mm
 65mm

 5/8" (15mm)
 100mm
 65mm



## ACROW-RICHMOND

THE HIDDEN STRENGTHT

LA FORCE CACHÉE

# EURO ROD



The AR Form Tie Bar is a high quality product used in industrial formwork systems, lost anchoring solutions, special connections and applications for cast in place and precast.

AR supplies a hot rolled, right flat deep thread bar, which assures the best effect for self cleaning after removal.

#### **TECHNICAL SPECIFICATION:**

	Imperial		Metric	
Diameter	5/8	inch	15	mm
Length	5.8	m	19	ft
Yield load min.	36,000	lb	160	kN
Rp 0.2 min.	130,500	psi	900	Мра
Ultimate load min.	44,000	lb	196	kN
Safe Working Load*	22,000	lb	98	kN
Rm min.	247,500	psi	1100	Мра
Lb/Ft	0.9	lb/Ft	1.4	kg/m
Elongation Agt	4	%	4	%
Elongation A10d	7	%	7	%
KCV min. at -20	28	J	28	J

\*SWL Provides a Safety Factor of 2:1

#### ALSO AVAILABLE FROM ACROW-RICHMOND:

#### **Distance Tube**

Available in 22 MM (7/8") ID x 2M (6'-1/2")



#### **Distance Cones**

22MM cone to fit distance tube 20MM cone to fit schedule 40 pipe



WWW.ACROW-RICMOND.COM