

Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

Section 1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Product Form Mixture Trade Name SPARKL-SEAL **Product Code** SP 1.2 Relevant identified uses of the substance or mixture and uses advised against Use Industrial. For professional use only. 1.2.2 Uses Advised Against No additional information available 1.3 Details of the supplier of the safety data sheet Manufacturer

NOX-CRETE MANUFACTURING INC 1444 SOUTH 20TH STREET **OMAHA, NE 68108** Tel: 402-341-2080 Fax: 402-341-9752 E-Mail: corporate@nox-crete.com Web Site: www.nox-crete.com

1.4 Emergency telephone number

Emergency Number

Chemtrec (800) 424-9300 Chemtrec Outside of U.S. 703-527-3887

Section 2. Hazards identification

Classification of the substance or mixture 2.1

Flam Liq. 3	H226
Asp. Tox. 1	H304
Acute Tox. 4 (dermal)	H312
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Acute Tox. 4 (inhalation	H332
resp. irrit. STOT SE 3	H335
STOT SE 3 drowsiness	H336
Carc. 2	H351
STOT RE 2	H373

Full text of H phrases see section 16 Adverse physiochemical, human health and environmental effects No additional information available 2.2 Label elements Hazard pictograms



Signal word Hazard statements

Danger H226 - Flammable liquid and vapor H304 - May be fatal if swallowed and enters airways

Flam Liq. 3



Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

Precautionary statements	 H312 - Harmful in contact with skin H315 - Causes skin irritation H319 - Causes serious eye irritation H332 - Harmful if inhaled H335 - May cause respiratory irritation H336 - May cause drowsiness or dizziness H351 - Suspected of causing cancer H373 - May cause damage to ears and CNS through prolonged or repeated exposure
Descention	Dood Obtain an acial instructions hafare use
Prevention:	 P201 - Obtain special instructions before use P202 - Do not handle until all safety precautions have been read and understood P210 - Keep away from heat/sparks/open flames/hot surfaces-No smoking P233 - Keep container tightly closed P240 - Ground/bond container and receiving equipment P241 - Use explosion-proof electrical/ventilating/light/equipment P242 - Use only non-sparking tools P243 - Take precautionary measures against static discharge P260 - Do not breathe dust/fume/gas/mist/vapors/spray P264 - Wash exposed area's thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area P280 - Wear protective gloves/protective clothing/eye protection/face protection
Response:	P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physicianP303+P361+P353 - IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / showerP304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.P305+P351+P338 -IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsingP308+P313 - IF exposed or concerned: Get medical advice/attention P331 - Do NOT induce vomitingP337+P313 - If eye irritation persists: Get medical advice/attention P370+P378 - In case of fire: Use Dry chemical, foam, carbon dioxide for
Storage:	extinction P403+P405+P235+P233 - Store locked up in a cool well ventilated
Disposal:	place. Keep container tightly closed. P501 - Dispose of contents/container in accordance with
	local/regional/national/international regulations.

2.3 Other hazards

Full text of R, H and EUH phrases: see section 16

Section 3. Composition / information on ingredients

3.1 Substances

Not applicable



According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

3.2 Mixture

Name	Product identifier	%
Xylene	1330-20-7	< 42.0
Solvent Naphtha	Trade Secret	Trade Secret
Ethylbenzene	100-41-4	< 12.0
1,2,4-Trimethylbenzene	95-63-6	< 12.0
Cumene	98-82-8	< 1.0

Pursuant to 29CFR 1910.1200(i) the specific chemical identity (and / or) concentration may be withheld as Trade Secret, while all health and safety properties and effects are included in the SDS.

Section 4. First aid measures

4.1 Description of first aid measures	
First-aid measures general	Get medical advice/attention if you feel unwell. Never give anything by
First-aid measures after inhalation	mouth to an unconscious person. If the individual experiences nausea, dizziness, has difficulty In breathing seek a healthcare professional immediately. In all cases of doubt, or when symptoms persist, seek medical advice. Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a Poison Center or doctor/physician.
First-aid measures after skin contact	If skin irritation persists, seek medical attention. Remove or take off immediately all contaminated clothing. Rinse skin with water or shower. Wash off immediately with soap and plenty of water.
First-aid measure after eye contact	When contact lenses are worn, remove if possible. In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes while holding eyelids apart. Get medical attention immediately.
First-aid measures after ingestion	Rinse mouth. DO NOT induce vomiting. Get medical attention immediately.
4.2 Most important symptoms and effects	
Symptoms/injuries after inhalation	May cause irritation to the respiratory tract. Overexposure to vapors may result in headache, nausea, drowsiness or dizziness.
Symptoms/injuries after skin contact	May cause skin irritation or burning sensation
Symptoms/injuries after eye contact	May cause eye irritation or injury
Symptoms/injuries after ingestion	May cause severe irritation or burns to the mucous membrane of the mouth, throat, esophagus and stomach
4.3 Indication of any immediate medical at	
No additional information available	

Section 5. Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	Dry chemical, foam, carbon dioxide
Unsuitable extinguishing media	Do not use heavy water stream
5.2 Special hazards arising from the subst	ance or mixture
Reactivity	Thermal decomposition products may cause a health hazard.
5.3 Advice for firefighters	



According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

Firefighting instructions	Flammable Liquid! This material releases vapors when heated above ambient temperatures. Vapors can cause a flash fire. Use water spray or fog to cool exposed containers.
Protective equipment for firefighters	Firefighters should always wear self-contained breathing apparatus (SCBA) and full protective gear when fighting any chemical fire.
Other information	On heating or burning harmful gasses/vapors may be released. This product may cause the floor to become slippery.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures		
General measures	Extremely Flammable. Eliminate any ignition sources. Dike or impound spilled material. Use Non-sparking tools. All equipment must be grounded. Take proper precautions to ensure your own health and safety before attempting spill control or cleanup.	
6.11 Protective Equipment	Equip cleanup crew with proper protective equipment.	
6.2 Environmental precautions	Prevent entry to sewers and public waters.	
	Notify authorities if liquid enters sewers or public waters.	
6.3 Methods and materials for containment and cleaning up		
Methods for cleaning up	Soak up spills with inert solids, such as clay or diatomaceous earth. Collect into vapor tight containers and dispose of properly.	

Section 7. Handling and storage

7.1 Precautions for safe handling			
Protective measures	Wash hands and other exposed areas with soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in work areas to prevent formation of vapor. When not in use keep containers tightly closed. Avoid breathing vapor or mist.		
Hygiene measures	Wash contaminated clothing before reuse.		
7.2 Conditions for safe storage, including any incompatibilities			
Storage conditions	Store in accordance with local regulations. Store in original container in a cool well ventilated place away from heat, sparks and open flame Keep containers tightly closed until ready for use.		
Incompatible materials Storage temperature	Strong oxidizing agents Store in a cool dry environment away from sources of ignition.		

Section 8. Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Ingredient name	Occupational exposure limits ACGIH TLV (United States)	
Xylene	TWA: 100 ppm 8 hours	
Solvent Naphtha	TWA: 19 ppm 8 hours	
Ethylbenzene	TWA: 20 ppm 8 hours	
Cumene	TWA: 50 ppm 8 hours	
1,2,4-Trimethylbenzene	TWA: 25 ppm 8 hours	
8.2 Exposure controls Appropriate engineering controls	Use with adequate ventilation to keep product vapor concentrations below specified TLV	
Eye and face protection	Chemical goggles and/or face shields are required to prevent potential eye contact, irritation or injury.	
Skin protection	Wear chemical resistant gloves and appropriate protective clothing and	



Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

boots as required to prevent skin contact. Wash exposed skin frequently with soap and water. Soiled clothing should be laundered before reuse.

Respiratory protection

General room ventilation is normally adequate. Avoid breathing the product mist or vapors. The use of an appropriate respirator is recommended whenever the airborne concentrations exceed the TLV.

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance C	clear liquid	
Odor S	trong Aromatic Odor	
Odor Threshold N	lo data available	
PH N	lo data available	
Melting point N	lo data available	
Freezing point N	lo data available	
Boiling point >	138 C (>280 F)	
Flash point 2	7 C 80 F PMCC	
Relative evaporation rate (butyl acetate=1) N	ite=1) No data available	
Flammability (solid, gas) F	lammable liquid and vapor	
Upper/lower explosive limits N	lo data available	
Vapor pressure N	lo data available	
Vapor density N	lo data available	
Relative density (Specific gravity) 0	.90 Kg per Liter 7.5 Lbs per Gallon	
Solubility W	Vater: Insoluble	
Partition coefficient n-octanol/water N	Defficient n-octanol/water No data available	
Auto-ignition temperature N	lot applicable	
,	lo data available	
VOC content	ess than 700 g/l	

Section 10. Stability and reactivity

<u>10.1</u>	Reactivity	No additional information available
10.2	Chemical stability	Stable under normal conditions
<u>10.3</u>	Possibility of hazardous reactions	Hazardous polymerization will not occur.
10.4	Conditions to avoid	Extreme high or low temperatures.
10.5	Incompatible materials	Strong acids and oxidizers
10.6	Hazardous decomposition products	carbon monoxide, carbon dioxide, various hydrocarbon derivatives

Section 11. Toxicology information

11.1 Information on toxicological effects Acute toxicity Irritation/Corrosion Skin Eyes Respiration or skin sensitization Germ cell mutagenicity Carcinogenicity IARC

Xylene	3
Ethylbenzene	2B
Cumene	2B

No adverse effects expected under intended use. May cause skin irritation May causes serious eye irritation and damage. May cause respiratory irritation No data available

2B - Limited evidence in humans and less than sufficient evidence in animals.

3 - Inadequate in humans and inadequate or limited in animals.



Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

Reproductive toxicity Specific target organ toxicity Single exposure Repeated exposure Aspiration hazard Section 12. Ecological information 12.1 Ecotoxicity 12.2 Persistence and degradability 12.3 Bioaccumulative potential 12.4 Mobility in soil 12.5 Other adverse effects	No data available No data available No data available May be fatal if swallowed and enters airways Not established Not established Not established Not established No additional information available Avoid release to the environment		
SECTION 13. Disposal Considerat	The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all applicable local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.		
SECTION 14. Transport information In accordance with ADR / RID / ADNR / IMDG <u>14.1 UN number</u> <u>14.2 UN proper shipping name</u> <u>14.3 Transport hazard class(es)</u> <u>14.4 Packing group</u> <u>14.5 Environmental hazards</u> <u>14.6 Special precautions for user</u> <u>14.7 Transport in bulk according to</u> <u>Annex II of MARPOL 73/78 and the IBC Code</u> <u>14.8 Transport in bulk according to</u> <u>CFR 49 173.15</u>	UN1263 Paint Related Material 3 III No additional information available		
SECTION 15. Regulatory information 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture 15.1.2 USA Regulations Section 313 Contains the following ingredients at or above the reporting level requirements of Section 313. This information must be included in all SDS's copied or distributed for this material.			
CHEMICAL Xylene Ethylbenzene 1,2,4-Trimethylbenzene Cumene TSCA Proposition 65	CAS #MAX WEIGHT %1330-20-7< 42.0100-41-4< 12.095-63-6< 12.098-82-8< 1.0All ingredients are listed or exemptedThis product contains one or more chemicals known to the State of California to cause cancer and/or reproductive toxicity.		



According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

DSL <u>15.2 Chemical safety assessment</u>

contains all of the information required by the HPR All ingredients are listed or exempted A Chemical Safety Assessment has not been carried out.

	Section	16.	Other information	
1.0				
_				

Date of issue	11-5-2015
Version	2.3
Number	100
Date of previous issue	5-13-2015
Preparer	Nox-Crete Manufacturing Inc.
D.C D	-

Reference Documentation

The information contained herein is based on data available to us and is believed to be correct. Since this information may have been obtained in part from independent laboratories or other sources not under our direct supervision, no representation is made that the information is accurate, reliable, complete or representative and Buyer may rely thereon only at Buyers risk. We have made no effort to censor or to conceal deleterious aspects of this product. Further since we cannot anticipate or control the many different conditions under which this information or our products may be used, we make no guarantee that the health and/or safety precautions we have suggested will be adequate for all individuals and /or situations involving its handling or use. Likewise, we make no guarantee or warranty of any kind that the use or disposal of this product is in compliance with all federal, state or local laws. It is the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

Disclaimer

The information in this document is believed to be correct as of the date issued. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of this use thereof. (NOX-CRETE MANUFACTURING INC)

Flam Liq. 3

Full text of R, H and EUH phrases

Flam Liq. 3	H226
Asp. Tox. 1	H304
Acute Tox. 4 (dermal)	H312
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Acute Tox. 4 (inhalation	H332
resp. irrit. STOT SE 3	H335
STOT SE 3 drowsiness	H336
Carc. 2	H351
STOT RE 2	H373

H226 - Flammable liquid and vapor

- H304 May be fatal if swallowed and enters airways
- H312 Harmful in contact with skin
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H332 Harmful if inhaled
- H335 May cause respiratory irritation
- H336 May cause drowsiness or dizziness
- H351 Suspected of causing cancer
- H373 May cause damage to ears and CNS through prolonged or repeated exposure



Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P210 - Keep away from heat/sparks/open flames/hot surfaces-No smoking

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical/ventilating/light/equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P264 - Wash exposed area's thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P303+P361+P353 - IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 -IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing

P308+P313 - IF exposed or concerned: Get medical advice/attention

P331 - Do NOT induce vomiting

P337+P313 - If eye irritation persists: Get medical advice/attention

P370+P378 - In case of fire: Use Dry chemical, foam, carbon dioxide for extinction

P403+P405+P235+P233 - Store locked up in a cool well ventilated place. Keep container tightly closed.

P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.